

# Correction in transient thermography inspection of blades

[blank line here]

by M. Rioux<sup>1</sup> and F. ROBY<sup>2</sup> [right aligned]

<sup>1</sup>Thermal Laboratory, University of Rimouski, 12345 Rimouski, Yourcountry; <sup>2</sup>EE Dept., Polytechnical School, D-70174 Göppingen, Germany [justified]

## Abstract

70 to 100 words abstract in 10 points with justified margins.

[blank line here]

**Keywords:** infrared thermography, blade inspection, corrosion assessment, global optimization, pulse scheme

[blank line here]

## 1. Introduction

Text is in 11 points with *justified margins* and 10 points space between all paragraphs and headings. The references are listed with 6 points only between them [1,2,3].

This is the second paragraph.

## 2. Theoretical aspects

This is an equation, written 1 in. = 2.5 cm from left margin [4]:

$$L = K^7 + a_{22} \cos \theta \quad (1)$$

Your text continues...

### 2.1. Experimental configuration

*Figure 1* shows the experimental set-up. [all the rest]

## 9. Acknowledgments

This work was supported by

[blank line here]

## REFERENCES

- [1] MALDAGUE (X.). - *Nondestructive evaluation of materials by infrared thermography*. London, Springer-Verlag, 224 p., 1993.
- [2] BALAGEAS (D.). - *Le contrôle non destructif par méthodes thermiques*. Rev. Gén. Therm. Fr., n° 356-357, Aug-Sept. 1991, p. 483-498. [in French]
- [3] ROBY (F.) and RIOUX (M.). - *Infrared thermographic inspection station: experimental set-up and working environment*. Bogdady (G.) ed., Proc. Industrial Automation Conf., Stuttgart, June 1-3, 1996, p. 22.5-22.7.